

**Technical Data Sheet**

**feldten marine Gelcoat Cleaner**

**Universal Alkaline Cleaner**

<b>Product description:</b>	feldten marine Gelcoat Cleaner is a high-tech water-based and ready-to-use alkaline cleaner for removing heavy soiling from gelcoat surface. It easily removes black stripes and other oxidation from a gelcoat surface. Can also be used on RIB.
<b>Suitable Substrates:</b>	Plastics, gelcoat, painted surfaces, metal. Test sensitive surfaces for compatibility.
<b>Material Base:</b>	Water-based detergent with organic ingredients.
<b>Packing:</b>	See current product and price list.
<b>Storage:</b>	Shelf life of at least 24 months in sealed original packing. In case of overstepping please check quality before use. Protect against heat, frost, and moisture.
<b>Application forms:</b>	Spread onto the surface and clean with sponge or brush.
<b>Colour:</b>	Colourless.
<b>Viscosity:</b>	< 10 mPas (at 20 °C)
<b>Consumption:</b>	As necessary, depending on level of soiling.
<b>Surface preparation:</b>	Not necessary.
<b>Product preparation:</b>	Product is ready for use.
<b>Application:</b>	feldten marine Gelcoat Cleaner is ready for use and should not be diluted. Spray with manual pump trigger directly onto the surface from an appropriate distance. If the surface is heavily soiled, let the product work some time. Remove soiling with a sponge, brush, or with a wet cloth. Rinse the surface with plenty of water and let dry.
<b>Application temperature:</b>	5 - 25 °C
<b>Drying:</b>	The cleaned surface can dry under ambient conditions. If necessary, wipe to a dry state.
<b>Tool cleaning (OEM):</b>	Rinse with water.
<b>Renewing and re-application:</b>	Use the cleaner as described above.
<b>Protective measures:</b>	While applying feldten marine Gelcoat Cleaner the signs and information on the label and the security and safety procedures recommended in the security data sheet should be considered, as well as the instructions of the respective Employers Liability Insurance Association for the prevention of accidents. Please follow MSDS.
<b>Waste management:</b>	See current material safety data sheet.
<b>VOC content:</b>	3 %

**Read carefully:** The information on this data sheet is based on the current status of technical development as well as our experience with the product. However, given the variety of surfaces and ambient conditions, the information provided on this data sheet shall in no way diminish the responsibility of the user to ensure with due care, that our product is suited for the intended purpose, surface and application conditions. Since application and processing lie outside our purview, no manufacturer liability shall be derived from the information provided herein. Our General Terms and Conditions of business shall apply in all cases. All information is subject to change without notice.

Nanogate Textile & Care Systems GmbH  
Zum Schacht 3  
D-66287 Göttelborn

Tel: +49 (0)6825 – 9591-0  
Fax: +49 (0)6825 – 9591-852  
E-Mail: [info@nanogate.com](mailto:info@nanogate.com)  
Homepage: [www.nanogate.com](http://www.nanogate.com)