

Article No.: 04000140 feldten marine Gelcoat Sealer UV+
Print date: 06.08.2020 Revision date: 30.01.2019
Version: 1.3 Issue date: 13.12.2016

EN
Page 1 / 9

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name/designation feldten marine Gelcoat Sealer UV+

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses:

Polish

1.3. Details of the supplier of the safety data sheet

supplier (manufacturer/importer/downstream user/distributor)

Nanogate Textile & Care Systems GmbH

Zum Schacht 3

D-66287 Göttingen

Telephone: +49 - (0)6825 / 9591 - 0

Telefax: +49 - (0)6825 / 9591 - 852

E-mail info@nanogate.com

Dept. responsible for information:

E-mail (competent person)

msds@nanogate.com

1.4. Emergency telephone number

111 (England, Wales, Scotland)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

Flam. Liq. 3 / H226

Flammable liquids

Flammable liquid and vapour.

Skin Sens. 1 / H317

Respiratory or skin sensitisation

May cause an allergic skin reaction.

Aquatic Chronic 3 / H412

Hazardous to the aquatic environment

Harmful to aquatic life with long lasting effects.

2.2. Label elements

The product is classified and labelled according to EC directives or corresponding national laws.

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



Warning

Hazard statements

H226

Flammable liquid and vapour.

H317

May cause an allergic skin reaction.

H412

Harmful to aquatic life with long lasting effects.

Precautionary statements

P210

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260

Do not breathe vapour.

P273

Avoid release to the environment.

P280

Wear protective gloves/protective clothing/eye protection/face protection.

P302 + P352

IF ON SKIN: Wash with plenty of soap and water.

P101

If medical advice is needed, have product container or label at hand.

P102

Keep out of reach of children.

P103

Read label before use.

Hazard components for labelling

glycidyl polydimethylsiloxane

Supplemental Hazard information (EU)

not applicable

2.3. Other hazards

No information available.

SECTION 3: Composition / information on ingredients

Article No.: 04000140 feldten marine Gelcoat Sealer UV+
Print date: 06.08.2020 Revision date: 30.01.2019
Version: 1.3 Issue date: 13.12.2016

EN
Page 2 / 9

3.2. Mixtures

Hazardous ingredients

Classification according to Regulation (EC) No 1272/2008 [CLP]

EC No. CAS No. INDEX No.	REACH No. Designation classification: // Remark	Wt %
918-481-9	01-2119457273-39 Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics Asp. Tox. 1 H304	1 < 3
203-492-7 107-46-0	01-2119496108-31 hexamethyl disiloxane Flam. Liq. 2 H225 / Aquatic Acute 1 H400 / Aquatic Chronic 2 H411	3 < 5
102782-97-8	glycidyl polydimethylsiloxane Skin Irrit. 2 H315 / Eye Irrit. 2 H319 / Skin Sens. 1 H317	3 < 5

Additional information

Full text of classification: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

Unsuitable extinguishing media

strong water jet

5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

5.3. Advice for firefighters

Provide a conveniently located respiratory protective device. Do not allow water used to extinguish fire to enter drains, ground or waterways. Cool closed containers that are near the source of the fire.

SECTION 6: Accidental release measures

Article No.: 04000140 feldten marine Gelcoat Sealer UV+
Print date: 06.08.2020 Revision date: 30.01.2019
Version: 1.3 Issue date: 13.12.2016

EN
Page 3 / 9

6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing agents. Do not use solvents.

6.4. Reference to other sections

Observe protective provisions (see section 7 and 8).

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advices on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Product may become electrostatically charged. Provide earthing of containers, equipment, pumps and ventilation facilities. Anti-static clothing including shoes are recommended. Floors must be electrically conductive. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

Further information

Vapours are heavier than air. Vapours form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSIVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (TRGS 727)".

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 15 °C and 30 °C. Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use. Read label before use.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values

not applicable

8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

Personal protection equipment

Respiratory protection

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190). Use only respiratory protection equipment with CE-symbol including four digit test number.

Recommended Respiratory protection: Respiratory protective device with half mask filter material type A. The standards EN 136, 140 and 405 of the European Commission for Standardization (CEN) make recommendations to respirators, the standards EN 149 and EN 143

Article No.: 04000140 feldten marine Gelcoat Sealer UV+
Print date: 06.08.2020 Revision date: 30.01.2019
Version: 1.3 Issue date: 13.12.2016

EN
Page 4 / 9

provide recommendations to respiratory filters.

Hand protection

For prolonged or repeated handling the following glove material must be used: Butyl caoutchouc (butyl rubber) / NBR (Nitrile rubber)

Thickness of the glove material \geq 0,7 mm

Breakthrough time (maximum wearing time) > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles EN ISO 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye/face protection

Wear closely fitting protective glasses in case of splashes.

Body protection

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

Protective measures

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

Environmental exposure controls

Do not allow to enter into surface water or drains. See section 7. No additional measures necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties *

Appearance:

Physical state:

Liquid

Colour:

milky

Odour:

characteristic

Odour threshold:

not applicable

pH at 20 °C:

2,5 / 100,0 Wt %

Method: DIN 19268

Melting point/freezing point:

not applicable

Initial boiling point and boiling range:

82 °C

Source: propane-2-ol

Flash point:

23 °C

Method: DIN 51755 part 1

Evaporation rate:

not applicable

flammability

Burning time (s):

not applicable

Upper/lower flammability or explosive limits:

Lower explosion limit:

0,8 Vol-%

Remark: Solvent

Upper explosion limit:

26 Vol-%

Remark: Solvent

Source: hexamethyl disiloxane

Vapour pressure at 20 °C:

2,2076 mbar

Vapour density:

not applicable

Relative density:

Density at 20 °C:

1,10 g/cm³

Method: DIN EN ISO 15212-1

Solubility(ies):

Water solubility (g/L) at 20 °C:

miscible

Partition coefficient: n-octanol/water:

see section 12

Auto-ignition temperature:

340 °C

Remark: Solvent

Source: hexamethyl disiloxane

Decomposition temperature:

not applicable

Article No.: 04000140 feldten marine Gelcoat Sealer UV+
Print date: 06.08.2020 Revision date: 30.01.2019
Version: 1.3 Issue date: 13.12.2016

EN
Page 5 / 9

Viscosity at 20 °C:	> 100 mPa*s Method: DIN 53019
Explosive properties:	not applicable
Oxidising properties:	not applicable
9.2. Other information	
Solvent separation test (%):	< 3 Wt % (ADR/RID)

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.

10.3. Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

10.4. Conditions to avoid

Hazardous decomposition byproducts may form with exposure to high temperatures.

10.5. Incompatible materials

not applicable

10.6. Hazardous decomposition products

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

SECTION 11: Toxicological information

Classification according to Regulation (EC) No 1272/2008 [CLP]

11.1. Information on toxicological effects

Acute toxicity

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

oral, LD50, Rat: > 5000 mg/kg

Method: OECD 401

dermal, LD50, Rabbit: > 5000 mg/kg

Method: OECD 402

inhalative (vapours), LC50, Rat: > 5000 mg/l (4 h)

Method: OECD 403

hexamethyl disiloxane

dermal, LD50, Rabbit: > 2000 mg/kg

Method: OECD 402

inhalative (vapours), LC50, Rat: 106 mg/l (4 h)

Method: OECD 403

oral, LD50, Rat: > 16 mL/kg

Skin corrosion/irritation; Serious eye damage/eye irritation

hexamethyl disiloxane

Skin, Rabbit (4 h)

Method: OECD 404

Not an irritant.

eyes, Rabbit: evaluation Not an irritant.

Method: OECD 405

Respiratory or skin sensitisation

May cause an allergic skin reaction.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

hexamethyl disiloxane

Germ cell mutagenicity; evaluation negative.

Method: OECD 471 (Ames test)

STOT-single exposure; STOT-repeated exposure

Article No.: 04000140 feldten marine Gelcoat Sealer UV+
Print date: 06.08.2020 Revision date: 30.01.2019
Version: 1.3 Issue date: 13.12.2016

EN
Page 6 / 9

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Practical experience/human evidence

Overall Assessment on CMR properties

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

Remark

There is no information available on the preparation itself .

SECTION 12: Ecological information

Classification according to Regulation (EC) No 1272/2008 [CLP]

Do not allow to enter into surface water or drains.

12.1. Toxicity

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Daphnia toxicity, EL0, Daphnia magna (Big water flea): 1000 (48 h)

Algae toxicity, EL0, Pseudokirchneriella subcapitata: 1000 (72 h)

Fish toxicity, LL0, Oncorhynchus mykiss (Rainbow trout): 1000 (96 h)

hexamethyl disiloxane

Fish toxicity, LC50, Oncorhynchus mykiss (Rainbow trout): 0,46 mg/l (96 h)

Method: OECD 203

Daphnia toxicity, EC50, Daphnia magna (Big water flea): > 0,37 mg/l (48 h)

Method: OECD 202

Algae toxicity, IC50:, Selenastrum capricornutum: > 0,55 mg/l (95 h)

Method: OECD 201

Growth test

Algae toxicity, IC10:, Selenastrum capricornutum: 0,14 mg/l (95 h)

Method: OECD 201

Growth test

Long-term Ecotoxicity

Harmful to aquatic life with long lasting effects.

hexamethyl disiloxane

Fish toxicity, NOEC, Cyprinus carpio (Common Carp): \geq 0,04 mg/l (56 D)

Method: OECD 305

Daphnia toxicity, NOEC, Daphnia magna (Big water flea): 0,08 mg/l (21 D)

Method: OECD 211

12.2. Persistence and degradability

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Biodegradation: 80 % (28 D); evaluation Readily biodegradable (according to OECD criteria).

hexamethyl disiloxane

Biodegradation, Biochemical oxygen demand: 2 % (28 D); evaluation Product is not easily biodegradable.

Method: OECD 301C/ ISO 9408/ EEC 92/69/V, C.4-F

12.3. Bioaccumulative potential

hexamethyl disiloxane

Partition coefficient: n-octanol/water: \geq 3

Bioconcentration factor (BCF)

hexamethyl disiloxane

Bioconcentration factor (BCF), Cyprinus carpio (Common Carp): 1290 - 2410

70 d; 0,04 mg/l

Bioconcentration factor (BCF), Cyprinus carpio (Common Carp): 776 - 1660

70 d; 0,004 mg/l

12.4. Mobility in soil

Toxicological data are not available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

Article No.: 04000140 feldten marine Gelcoat Sealer UV+
Print date: 06.08.2020 Revision date: 30.01.2019
Version: 1.3 Issue date: 13.12.2016

EN
Page 7 / 9

12.6. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Appropriate disposal / Product Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

List of proposed waste codes/waste designations in accordance with EWC

200129* Detergents containing hazardous substances

*Hazardous waste according to Directive 2008/98/EC (waste framework directive).

Appropriate disposal / Package Recommendation

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

SECTION 14: Transport information

14.1. UN number

UN 1993

14.2. UN proper shipping name

Land transport (ADR/RID):

Flammable liquid, n.o.s.
(Hexamethyldisiloxane)

Sea transport (IMDG):

FLAMMABLE LIQUID, N.O.S.
(Hexamethyldisiloxane)

Air transport (ICAO-TI / IATA-DGR):

Flammable liquid, n.o.s.
(Hexamethyldisiloxane)

14.3. Transport hazard class(es)

3

14.4. Packing group

III

14.5. Environmental hazards

Land transport (ADR/RID)

not applicable

Marine pollutant

not applicable

14.6. Special precautions for user

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

Further information

Land transport (ADR/RID)

tunnel restriction code

D/E

Sea transport (IMDG)

EmS-No.

F-E, S-E

Air transport (ICAO-TI / IATA-DGR)

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

VOC Switzerland:

weight fraction in %: 16,00

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830



Article No.: 04000140 feldten marine Gelcoat Sealer UV+
Print date: 06.08.2020 Revision date: 30.01.2019
Version: 1.3 Issue date: 13.12.2016

EN
Page 8 / 9

National regulations

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.
Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

15.2. **Chemical Safety Assessment**

For the following substances of this mixture a chemical safety assessment has been carried out:

EC No. CAS No.	Designation	REACH No.
918-481-9	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	01-2119457273-39

SECTION 16: Other information

Full text of classification in section 3:

Asp. Tox. 1 / H304	Aspiration hazard	May be fatal if swallowed and enters airways.
Flam. Liq. 2 / H225	Flammable liquids	Highly flammable liquid and vapour.
Aquatic Acute 1 / H400	Hazardous to the aquatic environment	Very toxic to aquatic organisms.
Aquatic Chronic 2 / H411	Hazardous to the aquatic environment	Toxic to aquatic life with long lasting effects.
Skin Irrit. 2 / H315	Skin corrosion/irritation	Causes skin irritation.
Eye Irrit. 2 / H319	Serious eye damage/eye irritation	Causes serious eye irritation.
Skin Sens. 1 / H317	Respiratory or skin sensitisation	May cause an allergic skin reaction.

Classification procedure

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Flam. Liq. 3	Flammable liquids	On basis of test data.
Skin Sens. 1	Respiratory or skin sensitisation	Calculation method.
Aquatic Chronic 3	Hazardous to the aquatic environment	Calculation method.

Abbreviations and acronyms

ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
OEL	Occupational Exposure Limit Value
BLV	Biological Limit Value
CAS	Chemical Abstracts Service
CLP	Classification, Labelling and Packaging
CMR	Carcinogenic, Mutagenic and Reprotoxic
DIN	German Institute for Standardization / German industrial standard
DNEL	Derived No-Effect Level
EAKV	European Waste Catalogue Directive
EC	Effective Concentration
EC	European Community
EN	European Standard
IATA-DGR	International Air Transport Association – Dangerous Goods Regulations
IBC Code	International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
ICAO-TI	International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous Goods by Air
IMDG Code	International Maritime Code for Dangerous Goods
ISO	International Organization for Standardization
LC	Lethal Concentration
LD	Lethal Dose
MARPOL	Maritime Pollution: The International Convention for the Prevention of Pollution from Ships
OECD	Organisation for Economic Cooperation and Development
PBT	persistent, bioaccumulative, toxic
PNEC	Predicted No Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
UN	United Nations
VOC	Volatile Organic Compounds
vPvB	very persistent and very bioaccumulative

Further information

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830



Article No.: 04000140 feldten marine Gelcoat Sealer UV+
Print date: 06.08.2020 Revision date: 30.01.2019
Version: 1.3 Issue date: 13.12.2016

EN
Page 9 / 9

EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in section 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.

* Data changed compared with the previous version